



Sizes			BYSTRÁ L 44 LD 440/570	BYSTRÁ L 44 LD 440/670
1	A	mm	440	
2	F	mm	1230	1330
3	C	mm	465	
4	DN	Ø mm	180	
5	B	mm	570	670
6	FF	mm		
7	V	mm	550	
8	AA	mm		
9	H	mm		
10	J	mm	325 + /160/	
11	K	Ø mm	4x125	
12	L	Ø mm	125	
13	M	mm		
14	N	mm	50	

Basic design:

Thermodynamic Hearth
 Segment chamotte lining SO
 Glass Classic
 Inox control grip-handle RP2
 Environmentally friendly varnish

Technical parameters			
1	Nominal heat output	kW	8,0
2	Pressure required	Pa	12
3	Average efficiency	%	77,8
4	Average flue gas temperature	°C	296
5	Wood consuption	kg/h	2,5
6	Consumption of combustion air	m3/h	24
7	Emission of CO to 13% O2	%	0,1
8	Flue gas mass flow	g/s	7,6
9	Weight	kg	180
10	Required min. cross section for circulating air - INPUT	cm ²	250
11	Required min. cross section for circulating air - OUTPUT	cm ²	400
12	Three-component insulated chimney - active height 5 m	Ø cm	180
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	Yes

Optional accessories:

Cover frame (KR)
 Glass Reflex (SR)
 Black printed glass(SM)
 External ashtray (VOP)
 Lower hearth (ZO)
 Convectional casing (DP)
 Vertical heat-storing panel (AZ)
 Heat accumulation quadrant (APO)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk