



combustion air inlet

**Basic design:**

Thermodynamic Hearth  
 Segment chamotte lining SO  
 Glass Classic  
 Inox control grip-handle 2xRP2  
 Environmentally friendly varnish

Sizes			BYSTRÁ O 60 LD 600/790	BYSTRÁ O 60 LD 600/910
1	A	mm	600	
2	F	mm	1470	1590
3	C	mm	570	
4	DN	Ø mm	200	
5	B	mm	790	910
6	FF	mm		
7	V	mm	750	
8	AA	mm		
9	H	mm		
10	J	mm	325 + /160/	
11	K	Ø mm	4x125	
12	L	Ø mm	125	
13	M	mm		
14	N	mm	50	

**Optional accessories:**

Cover frame (KR)  
 Glass Reflex (SR)  
 Black printed glass(SM)  
 External ashtray (VOP)  
 Lower hearth (ZO)  
 Convectional casing (DP)  
 Rear feeding door (DPS,DPSO)  
 Vertical heat-storing panel (AZ)  
 Heat accumulation quadrant (APO)

Technical parameters			
1	Nominal heat output	kW	12,5
2	Pressure required	Pa	12
3	Average efficiency	%	76,8
4	Average flue gas temperature	°C	271
5	Wood consumption	kg/h	3,9
6	Consumption of combustion air	m <sup>3</sup> /h	37,5
7	Emission of CO to 13% O <sub>2</sub>	%	0,1
8	Flue gas mass flow	g/s	13,8
9	Weight	kg	270
10	Required min. cross section for circulating air - INPUT	cm <sup>2</sup>	375
11	Required min. cross section for circulating air - OUTPUT	cm <sup>2</sup>	625
12	Three-component insulated chimney - active height 7 m	Ø cm	180
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	Yes

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk