


combustion air inlet

	Sizes		CHOPOK L 130	CHOPOK L 130	CHOPOK L 130
			VD 1370/450	VD 1370/510	VD 1370/570
1	A	mm	1370		
2	F	mm	1400	1460	1520
3	C	mm	565		
4	DN	Ø mm	225		
5	B	mm	450	510	570
6	FF	mm	1350	1470	1590
7	V	mm	1480		
8	AA	mm			
9	H	mm	315	375	435
10	J	mm	325 + /160/		
11	K	Ø mm	4x125		
12	L	Ø mm	2x125		
13	M	mm	20		
14	N	mm			

Basic design:

Thermodynamic Hearth
 Segment chamotte lining (SO)
 Glass Classic
 Inox control grip-handle MP2
 Enviromentally friendly varnish



Technical parameters			
1	Nominal heat output	kW	16,0
2	Pressure required	Pa	12
3	Average efficiency	%	78,1
4	Average flue gas temperature	°C	261
5	Wood consupction	kg/h	5,2
6	Consumption of combustion air	m3/h	48
7	Emission of CO to 13% O2	%	0,1
8	Flue gas mass flow	g/s	18,4
9	Weight	kg	470
10	Required min. cross section for circulating air - INPUT	cm ²	500
11	Required min. cross section for circulating air - OUTPUT	cm ²	800
12	Three-component insulated chimney - active height 6 m	Ø cm	250
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	No

Optional accessories:

Cover frame (KR)
 Glass Reflex (SR)
 Black printed glass(SM)
 Black printed glass Reflex (SMR)
 External ashtray (VOP)
 Lower hearth (ZO)
 Convectional casing (DP)
 Vertical heat-storing panel (AZ)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk