



Sizes			CHOPOK 2R90 60 LD 600/450- S/450	CHOPOK 2R90 60 LD 600/510- S/450	CHOPOK 2R90 60 LD 600/570- S/450
1	A	mm		600	
2	F	mm	1300	1360	1420
3	C	mm		465	
4	DN	Ø mm		180	
5	B	mm	450	510	570
6	FF	mm			
7	R	mm		450	
8	AA	mm			
9	H	mm			
10	J	mm		325 + /160/	
11	K	Ø mm		4x125	
12	L	Ø mm		125	
13	M	mm			
14	N	mm		50	

Basic design:

Thermodynamic Hearth
Segment chamotte lining (SO)
Glass Classic
Inox control grip-handle RP1A
Environmentally friendly varnish



Technical parameters			
1	Nominal heat output	kW	9,0
2	Pressure required	Pa	12
3	Average efficiency	%	77,3
4	Average flue gas temperature	°C	263
5	Wood consumption	kg/h	3
6	Consumption of combustion air	m ³ /h	27
7	Emission of CO to 13% O ₂	%	0,1
8	Flue gas mass flow	g/s	10,3
9	Weight	kg	175
10	Required min. cross section for circulating air - INPUT	cm ²	275
11	Required min. cross section for circulating air - OUTPUT	cm ²	450
12	Three-component insulated chimney - active height 5 m	Ø cm	160
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	Yes

Optional accessories:

Cover frame (KR) - divided SS
Glass Reflex (SR)
Black printed glass (SM)
Black printed glass Reflex (SMR)
External ashtray (VOP)
Vermiculite lining (VO)
Lower hearth (ZO)
Convictional casing (DP)
Vertical heat-storing panel (AZ)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BImSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk