


Sizes		CHOPOK LE 78 VD 850/630	
1	A		850
2	F	mm	1605
3	C	mm	610
4	DN	Ø mm	200
5	B	mm	630
6	FF	mm	1710
7	V	mm	960
8	AA	mm	
9	H	mm	460
10	J	mm	325 + /160/
11	K	Ø mm	4x125
12	L	Ø mm	125
13	M	mm	20
14	N	mm	

Basic design:

Thermodynamic Hearth
 Segment chamotte lining SO
 Glass Classic
 Inox control grip-handle MP2
 Enviromentally friendly varnish



Technical parameters			
1	Nominal heat output	kW	12,0
2	Pressure required	Pa	12
3	Average efficiency	%	76,9
4	Average flue gas temperature	°C	286
5	Wood consuption	kg/h	3,9
6	Consumption of combustion air	m ³ /hod	36
7	Emission of CO to 13% O2	%	0,1
8	Flue gas mass flow	g/s	12,2
9	Weight	kg	370
10	Required min. cross section for circulating air - INPUT	cm ²	375
11	Required min. cross section for circulating air - OUTPUT	cm ²	600
12	Three-component insulated chimney - active height 6 m	Ø cm	200
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	No

Optional accessories:

Cover frame (KR)
 Glass Reflex (SR)
 Black printed glass(SM)
 Double glass Modern(DSM)
 Lower hearth (ZO)
 External ashtray (VOP)
 Convectional casing (DP)
 Rear feeding door (PD)
 Vertical heat-storing panel (AZ)
 Heat accumulation quadrant (APO)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk