



Sizes		CHOPOK R90 55 VD 600/450- S/380(L/P)	CHOPOK R90 55 VD 600/510- S/380(L/P)	CHOPOK R90 55 VD 600/570- S/380(L/P)	
1	A	mm	600		
2	F	mm	1300	1360	1420
3	C	mm	480		
4	DN	Ø mm	180		
5	B	mm	450	510	570
6	FF	mm	1350	1470	1590
7	R	mm	380		
8	V	mm	655		
9	H	mm	315	375	435
10	J	mm	325 + /160/		
11	K	Ø mm	2x125		
12	L	Ø mm	125		
13	M	mm	20		
14	N	mm			

Basic design:

Thermodynamic Hearth
Segment chamotte lining (SO)
Glass Classic
Inox control grip-handle MP2
Environmentally friendly varnish



CHOPOK R90 -S/380 P



CHOPOK R90 -S/380 L

Technical parameters			
1	Nominal heat output	kW	8,0
2	Pressure required	Pa	12
3	Average efficiency	%	81,9
4	Average flue gas temperature	°C	237
5	Wood consuption	kg/h	2,9
6	Consumption of combustion air	m3/h	24
7	Emission of CO to 13% O2	%	0,1
8	Flue gas mass flow	g/s	7,9
9	Weight	kg	230
10	Required min. cross section for circulating air - INPUT	cm ²	250
11	Required min. cross section for circulating air - OUTPUT	cm ²	400
12	Three-component insulated chimney - active height 5 m	Ø cm	160
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	No

Optional accessories:

Cover frame (KR)
Glass Reflex (SR)
Black printed glass(SM)
Black printed glass Reflex (SMR)
External ashtray (VOP)
Lower hearth (ZO)
Vertical heat-storing panel (AZ)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

 KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk