



Sizes			ROTO 400 480/275	ROTO 400 480/325	ROTO 400 530/325
1	A	mm	275	325	325
2	F	mm	1200		
3	C	mm	505		
4	DN	Ø mm	160		
5	B	mm	480	480	530
6	V	mm	465	465	515
7	FF	mm			
8	AA	mm			
9	N	mm	80		
10	J	mm	325 + /160/		
11	K	Ø mm			
12	L	Ø mm	100		

Basic design:

Thermodynamic Hearth
 Vertical Fireclay VS
 Glass Classic
 Inox control grip-handle RP2
 Environmentally friendly varnish

Technical parameters			
1	Nominal heat output	kW	7,5
2	Pressure required	Pa	12
3	Average efficiency	%	81,2
4	Average flue gas temperature	°C	251
5	Wood consumption	kg/h	2,2
6	Consumption of combustion air	m ³ /h	22,5
7	Emission of CO to 13% O ₂	%	0,1
8	Flue gas mass flow	g/s	6,8
9	Weight	kg	120
10	Required min. cross section for circulating air - INPUT	cm ²	225
11	Required min. cross section for circulating air - OUTPUT	cm ²	375
12	Three-component insulated chimney - active height 4 m	Ø cm	160
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	Yes

Optional accessories:

Cover frame (KR)
 Glass Reflex (SR)
 Black printed glass(SM)
 Heat accumulation quadrant (APO)